



STORM

Bottom-Load Cooler



Our new Bottom-Load water dispenser – the Storm C&C, dispensing cold & ambient water – is the latest model in the Crystal Mountain's line of coolers. The Bottom-Load means no more lifting heavy bottles in any environment, just open the front door and the bottle slides into the base of the cooler with little effort. The Storm features an easy to remove reservoir system, that takes less than a minute to change. The LED indicator tells you when it needs to be replaced. Servicing has never been easier. With its contemporary design, attractive finish, concealed faucets and easy maintenance, the Storm is sure to dazzle in any environment.

Storm: Hot & Cold



Concealed Water Outlet



Removable Drip Tray



Replaceable Reservoir System
SmartFlo™ Water Cartridge



Unique Sliding
Front Door

ITEM

SPECIFICATIONS

Power rating		Single phase
		100-115VAC, 60Hz
Standard current		Hot & Cold : 4.8~5.3A
Power	Cold	70W
Consumption	Hot	500W
Cold	Compressor	Single phase motor
	Refrigerant	R134a
	Temp range	4-10°C(39.2-50°F)
	Temp control	thermostat (ON 8 °C ±1.5°C, OFF 4 °C ±1.5°C)
	Volume of Cold Reservoir	1.6L (0.4 gal)
Hot	Heater	Internal heater
	Temp range	76-92°C (168.8-197.6°F)
	Safety device	Bimetal (Auto reset: 93 °C OFF)
	Temp control	Bimetal (85°C)(185°F)
	Capacity (Internal Heater)	1.1L (0.3 gal)
Refrigerant charge		32g(1.13 oz)
Noise(sound power level)		Pump:50dB(A); Compressor:43dB(A)
Product weight		Hot & Cold: 14.5kg (32.0 lb)
Product boxed weight		Hot & Cold: 16.2kg (35.7 lb)
Product dimensions		320(W) x 340(D) x 1116(H)mm 12.6"(W) X 13.4"(D) X 43.9"(H)
Product boxed dimensions		340(W) X 380(D) X 1165(H)mm 13.4" (W) X 15.0" (D) X 45.9" (H)
Loading quantity		20' Container: 204 Units 40' Container: 420 Units
IEC protection class		Class 1
Certifications		UL, EnergyStar, NSF372
Warranty		Three year