




# EVEREST

## POU Water Cooler



Crystal Mountain is taking cooling the waters of the world to new heights with the introduction of the Everest. Its sleek two toned aesthetic will enhance any space. The sturdy and ergonomic faucet handles are 177.8mm (7 inches) higher than traditional units, which enable effortless dispensing. The quickly removable side panels facilitate access to all electrical components for easy maintenance and servicing. The innovative removable reservoir and faucet assembly make the cleaning and sanitizing process fast and simple. Crystal Mountain proves that anything is possible when there is a drive to overcome all obstacles.

### Everest : Hot & Cold



Sturdy Metal Faucet Handles



Removable Reservoir/Faucet Assembly (patent pending)



Retrofitted to Become a Point of Use Dispenser

### ITEM

### SPECIFICATIONS

Power rating		Single phase (220-240VAC 50Hz)
Standard current		H&C: 2.5~2.8A
Power	Cold	80W
Consumption	Hot	450W
Cold	Compressor	Single phase motor
	Refrigerant	R600a
	Temp range	4-10°C(39.2-50°F)
	Temp control	thermostat (ON 12°C±1.5°C, OFF 2°C±1.5°C)
	Capacity	2.35L (0.6gal)
Hot	Heater	Band heater
	Temp range	74-92°C (165.2-197.6°F)
	Safety device	Bimetal (Manual reset: 95°C OFF)
	Temp control	Bimetal (83°C)(181.4°F)
	Capacity (External Heater)	1.1L (0.3 gal)
Refrigerant charge		13g (0.45 oz)
Noise(sound power level)		44dB(A)
Product weight		H&C: 12.2 kg (27.0 lb)
Product boxed weight		H&C: 13.5 kg (29.8 lb)
Product dimensions		358.5(W) X 342(D) X 1053(H)mm 14.1"(W) X 13.5 "(D) X41.4"(H)
Product boxed dimensions		330(W) X 330(D) X 1070(H)mm 13.0"(W) X 13.0 "(D) X 42.1"(H)
Loading quantity		20' Container: 320Units 40' Container: 640Units
IEC protection class		Class 1
Certifications		C-UL-US, CE, CB

#### Cup dispenser version

Product weight	H&C: 12.6 kg (27.7 lb)
Product boxed weight	H&C: 13.9 kg (30.7 lb)
Product dimensions	358.5(W) X348(D) X1053(H)mm
	14.1"(W) X 13.7"(D) X 41.4"(H)