



# STORM

## POU Water Cooler



Our new Bottom-Load water dispenser – the Storm C&C, dispensing cold & ambient water – is the latest model in the Crystal Mountain's line of coolers. The point of use conversion kit is easily installed by opening the front door and sliding it into the base of the cooler with little effort. The Storm features an easy to remove reservoir system, that takes less than a minute to change. The LED indicator tells you when it needs to be replaced. Servicing has never been easier. With its contemporary design, attractive finish, concealed faucets and easy maintenance, the Storm is sure to dazzle in any environment.

### Storm: Hot & Cold



Concealed Water Outlet



Removable Drip Tray



Replaceable Reservoir System  
SmartFlo™ Water Cartridge



Unique Sliding  
Front Door

### ITEM

### SPECIFICATIONS

Power rating		Single phase
		220-240VAC, 50Hz
Standard current		Cook&Cold: 1.0~1.2A
Power	Cold	70W
Consumption		
Cold	Compressor	Single phase motor
	Refrigerant	R600a
	Temp range	4-10°C(39.2-50°F)
	Temp control	thermostat (ON 8 °C ±1.5°C, OFF 4 °C ±1.5°C)
Volume of Cold Reservoir		1.6L (0.4 gal)
Refrigerant charge		16g(0.564 oz)
Noise(sound power level)		Pump:50dB(A); Compressor:43dB(A)
Product weight		Cook&Cold: 14.5kg (31.0 lb)
Product boxed weight		Cook&Cold: 15.7kg (35.0 lb)
POU assembly weight		2.0kg(4.5 lb)
POU assembly boxed weight		2.6kg(5.7 lb)
Product dimensions		320(W) x 340(D) x 1116(H)mm
		12.6"(W) X 13.4"(D) X 43.9"(H)
Product boxed dimensions		340(W) X 380(D) X 1165(H)mm
		13.4" (W) X 15.0" (D) X 45.9" (H)
Loading quantity		20' Container: 204 Units
		40' Container: 420 Units
IEC protection class		Class 1
Certifications		C-UL-US, CE, CB