



***CrystalFlo Water Cartridge
Replacement***

Replacement of CrystalFlo Water Cartridge

A flashing yellow light above the faucet levers will alert you to when the CrystalFlo Water Cartridge should be replaced. The system has been pre-set to provide indication after a period of 12 months of use. User may operate the cooler as normal until the bottle has been emptied. It is also advised to replace the CrystalFlo cartridge if there is a leak from the cartridge, taste problem or discoloration to the water.

Note: To reset the life timer system, the CrystalFlo is required to be removed from the dispenser for a minimum of 15 seconds while the unit is connected to the mains power supply.

1. Place a glass or other container below the water outlets (to catch drips)(Figure 1), and unlatch the Top Cover Locking Clip (located inside of the Bottle Installation area)(Figure 2), and open Top Cover (Figure 3).
2. Pull CrystalFlo Water Cartridge upwards to remove (Figure 4) . Do not squeeze the water reservoir as water could leak out. In addition, it may be helpful to have a bucket nearby to place the used CrystalFlo in.




Figure 1




Figure 2




Figure 3




Figure 4

3. Please recycle the CrystalFlo whenever possible, otherwise dispose of responsibly
4. Ensure seal is properly installed on the Inlet/Outlet tube of the CrystalFlo Water Cartridge assembly (may have shifted during shipment or un-packaging)
5. Align CrystalFlo Water Cartridge with openings in cooler, and push downwards into place (Figure 5). Ensure that foam seal is pushed down and seals the reservoir completely.
6. Close the top cover (push downwards to lock into place) (Figure 6 and Figure 7). If cover does not close completely, make sure that CrystalFlo is inserted completely.
7. Install replacement bottle (Figure 8)

Note: To prevent water leaks, a **NON-SPILL Bottle Cap MUST** be installed on the bottle.

8. Prime water system (See K2 Quick Start guide "Prime Water System" for instructions if needed.)




Figure 5




Figure 6



Figure 7




Figure 8

The customer acknowledges that water, like other liquids, can cause damage to surfaces. The customer takes full responsibility for placing the cooler within a residence or business, and acknowledges that failure to address drips, leaks or spillages is at the customer's risk.

The Warranty and Intertek Testing Services (ETL) and CE listings for the coolers are invalidated if any alteration, modification, or use or misuse in combination with any other machine or devices is deemed to be the source of any claim. The manufacturer accepts no liability (including for bodily injury) resulting from any alteration, misuse, neglect, accidents, improper installations or repairs.

For more information on this product, please visit www.crystalcoolers.com