

CRYSTAL MOUNTAIN PRODUCT BROCHURE



ASPEN
POU Water Cooler

ASPEN

POU Water Cooler



PEAK PERFORMANCE AT A VALUE PRICE

The Aspen is the perfect water cooler for the traditional home and office delivery. Featuring Stainless tanks and one-piece blow moulded cabinet, the Aspen is built to perform and backed by the company known for innovation, quality and support.

Features

- Black and White cabinet options
- Hot & Cold or Cook & Cold models
- #304 stainless cold reservoir
- #304 stainless hot tank
- #304 stainless waterways
- One piece blow moulded polyethylene cabinet
- Internal frame self supporting frame
- ENERGY STAR™ certified



Removable Drip Tray



Carry Handle



ASPEN

POU Water Cooler

Performance and Specifications

General

Air cooled, POU type water cooler

Cooler Cabinet

Black or white, one-piece, moulded, polyethylene cabinet

Faucet Type

Polypropylene (PP) faucet with self closing handle. Hot Faucet includes a Child Resistant Handle which requires dual action to activate

Cold Water Tank Specifications

Stainless steel #304 or HDPE casing with 3.47L (0.9 gal) volume

Cold water cooling capacity of 2.0L/hr (0.5 gal/hr) based on 21°C (69.8°F) room temperature

Cold Water Thermostat

Preset at factory to dispense water at temperature from 4-10°C (39.2-50°F)

Adjustable cold control located at the back of the cabinet

Hot Water Tank Specifications

Stainless steel #304 casing with 2.0L (0.5 gal) volume

Hot water capacity of 4.5L/hr (1.2 gal/hr) based on 21°C (69.8°F) room temperature

Hot Water Thermostats and Heater

Automatic thermostat control with temperature range of 74-92°C (165.2-197.6°F)

Manual safety reset in case of automatic thermostat failure

450W external mica-heater band

ON/OFF switch is located at the back of the cabinet

Electronic Thermostat System (ETS) is available, which provides for a temperature control range of 88-92°C (190.4-197.6°F)

Compressor Type

Hermetically sealed reciprocating compressor

220-240VAC 50Hz, 100-115VAC 60Hz

Refrigerant Type: R134a (CFC Free)

Refrigerant Charge: 34g (1.2 oz)



Dimensions and Freight Data

Model	Products Dimensions WxDxH (mm/in.)	Box Dimensions WxDxH (mm/in.)	Product Weight (kg/lb)		Product Boxed Weight (kg/lb)		Loading Qty	
							20FT	40FT
Aspen POU Water Cooler	320x320x980mm	330x330x1000mm	H&C:12.0kg	C&C:11.5kg	H&C:13.0kg	C&C:12.5kg	238 units	504 units
	12.6"x12.6"x38.6"	12.8"x12.8"x39.4"	(25.6 lb)	(25.4 lb)	(28.6 lb)	(27.6 lb)		

All performances are tested in a controlled environment, certified by a third party. To learn more about these standards, please speak to your Crystal Mountain representative.



Crystal Mountain

Crystal Mountain Products Limited

European Sales Office

Fence House, Fence Avenue
Macclesfield, Cheshire
United Kingdom SK10 1LT
Tel: +44(0) 1625 439 111
Fax: +44 (0) 1625 502 527

E-mail: cmeurope@crystalcoolers.com

North American Sales Office

200 Carnegie Drive, Suite 234
St. Albert, AB, T8N 5A7 Canada
Toll Free: 800 878 6422
Tel: 1 780 454 4545

E-mail: sales@crystalcoolers.com

Crystal Mountain Products Inc.

US Office / Warehouse

1665 Westbelt Drive
Columbus, Oh 43228
Outbound Door #2
Tel: (614) 454 1618
Fax:(614) 409 9782

E-mail: sales@crystalcoolers.com

Crystal Mountain International Limited

Hong Kong Sales Office

Room 610, Winfield Commercial Building
6-8a Prat Avenue, Tsimshatsui
Kowloon, Hong Kong
Tel: (852) 2368 1989
Fax: (852) 3017 6727

E-mail: cmasia@crystalcoolers.com



Website: www.crystalcoolers.com

Crystal Mountain has a policy of continuous development and reserves the right to change specifications without notification.

