


AVALANCHEBottled Water Cooler



The small footprint Avalanche water cooler is designed to fit conveniently on a kitchen or office countertop. The compressor in this compact design provides exceptional cooling rates and runs very quietly. This Avalanche is available as Cold and Cold, or Hot and Cold, and has handy LED lights indicating when water reaches temperature. Also available as a Point-of-Use (Plumbed In) unit.

Avalanche: Hot & Cold







LED display

ITEM

SPECIFICATIONS

| Power rating | | Single phase 100-115VAC 60Hz H&C: 6.2A 74W 450W Single phase motor R134a 4-10°C(39.2-50°F) | |
|--------------------------|----------------------------|--|--|
| 1 Ower raung | | 100-115VAC 60Hz | |
| Standard current | 100-115VAC | H&C: 6.2A | |
| Power | Cold | 74W | |
| Consumption | Hot | 450W | |
| Cold | Compressor | Single phase motor | |
| | Refrigerant | R134a | |
| | Temp range | 4-10°C(39.2-50°F) | |
| | Capacity | 1.1L (0.3 gal) | |
| Hot | Temp control | Bimetal 74-92°C (165.2-197.6°F) | |
| | Capacity (Internal Heater) | 1.5L (0.4 gal) | |
| Refrigerant charge | | 30g (1.06 oz) | |
| Product weight | | Hot&Cold: 11.6 kg (25.6 lb) | |
| Product boxed weight | | Hot&Cold: 12.6 kg (27.7 lb) | |
| Product dimensions | | 330(W) X 368(D) X 419(H)mm | |
| Product dimensions | | H&C: 6.2A 74W 450W Single phase motor R134a 4-10°C(39.2-50°F) 1.1L (0.3 gal) Bimetal 74-92°C (165.2-197.6°F) r) 1.5L (0.4 gal) 30g (1.06 oz) Hot&Cold: 11.6 kg (25.6 lb) Hot&Cold: 12.6 kg (27.7 lb) | |
| Product boxed dimension | 20 | 370(W) X 380(D) X 450(H)mm | |
| Froduct boxed difficults | | 14.6"(W) X 15.0"(D) X 17.7"(H) | |
| Loading quantity | | 20' Container: 450 Units | |
| | | 40' Container: 960 Units | |
| IEC protection class | | Class 1 | |
| Certifications | | C-UL-US, CE, CB | |