



K2 Bottled Water Cooler



The K2 is the latest in Crystal Mountain's pursuit of modern appliance design. It features the revolutionary CrystalFlo™ Water Cartridge which is a removable reservoir system. The CrystalFlo™ can be easily removed and replaced as part of regular sanitization. All water contact components are simply replaced rather than being cleaned, which ensures 100% sanitization. The K2 has been designed with an ergonomic high dispense point, almost 12 inches (30cm) higher than traditional top load bottled water coolers. The recessed water outlet, the increased dispensing rate and the large dispensing area add to an enhanced user experience. The design and look of the K2 will improve customer retention and new customer acquisitions and the CrystalFlo™ water cartridge will simplify the cooler refurbishment process and provide repeat retail sales.

K2 : Hot & Cold



LED Indicator Lights and
Power Saving Mode
Sensor



Removable Cooler Base



CrystalFlo™ - Replaceable
Reservoir System

ITEM

SPECIFICATIONS

Power rating	Single phase (220-240VAC 50Hz)	
Standard current	220-240VAC	Hot & Cold: 2.5~2.8A
	100-115VAC	Hot & Cold: 4.3~4.8A
Power	Cold	75W
Consumption	Hot	450W
Cold	Compressor	Single phase motor
	Refrigerant	R134a
	Temp range	4-10°C (39.2-50°F)
	Temp control	Thermistor
	Capacity	2.1L (0.6 gal)
Hot	Heater	Band heater
	Temp range	74-92°C (165.2-197.6°F)
	Safety device	Manual reset: 98°C OFF
	Temp control	Thermistor
	Capacity (External Heater)	1.1L (0.3 gal)
Refrigerant charge	35g (1.2 oz)	
Noise(sound power level)	44dB(A)	
Product weight	Hot & Cold: 12.8kg (28.2 lb)	
Product boxed weight	Hot & Cold: 13.8 kg (30.4 lb)	
Product dimensions	358.7(W) X347.3(D) X1053(H)mm	
	14.1"(W) X 13.7"(D) X 41.4"(H)	
Product boxed dimensions	290(W) X 285(D) X 1080(H)mm	
	11.4"(W) X 11.2 "(D) X 42.6"(H)	
Loading quantity	20' Container: 320 Units	
	40' Container: 640 Units	
IEC protection class	Class 1	
Certifications	C-ETL-US	