



# GLACIER

## POU Water Cooler



The Glacier Point of Use water dispenser is available in Hot and Cold or Cook and Cold models. The rounded cabinet and fluted front give the Glacier a classic Greek column design suitable for any environment. While being aesthetically pleasing, the polyethylene cabinet smooth finish is easy to clean and refurbish. This commercial grade cooler will deliver years of trouble free optimum performance.

### Glacier: Hot & Cold



PP Faucet with self closing handle



Hot water ON and OFF switch



Removable drip tray

## ITEM

## SPECIFICATIONS

Power rating		Single phase
		100-115VAC 60Hz
Standard current		Hot & Cold: 6.2A
Power	Cold	74W
Consumption	Hot	450W
Cold	Compressor	Single phase motor (TS24 LATG)
	Refrigerant	R134a
	Temp range	4-10°C(39.2-50°F)
	Capacity	2.8L (0.6 gal)
Hot	Heater	Internal Heating Element
	Temp range	74-92°C (165.2-197.6°F)
	Temp control	82-89°C (179.6-192.2°F)
	Capacity (External Heater)	2L (0.5 gal)
	Capacity (Internal Heater)	1L (0.3 gal)
Refrigerant charge		27g(0.95 oz)
Product weight		Hot & Cold: 13.7kg (30.1 lb)
Product boxed weight		Hot & Cold: 14.8kg (32.6 lb)
Product dimensions		312(W) X 314(D) X 980(H)mm 12.2"(W) X 12.4"(D) X 38.6"(H)
Product boxed dimensions		320(W) X 330(D) X 1000(H)mm 12.5"(W) X 13.0"(D) X 39.4"(H)
Loading quantity		20' Container: 252 Units 40' Container: 518 Units
IEC protection class		Class 1
Certifications		C-UL-US, CE, CB, CCC